

Paring Machine

**Type DSMT (Table model)**



## Open machine for knife exchange



Flange bolting  
with Ø 35 mm



Central clamping  
with Ø 50 mm

Knife execution 1  
(Front side)



Knife execution 2  
(Front side)



## **Sturdy steel construction with following features:**

- Machine for screw-on of a work table, maximum plate thickness 40 mm
- Drive motor with belt tensioning device will be mounted under the working plate and screwed with the machine
- Knife / flange drive via special belt inside closed housing
- Folding machine frame for easy and fast knife exchange
- 2 universal knife guards, easy adjustable
- Flange and drive components ball bearing mounted -absolutely maintenance-free-
- Half-closed knife run and pressure bolster on operating side
- Optional with circular knife for flange bolting with internal bore Ø 35 mm or with circular knife for central clamping with internal bore Ø 50 mm
- Flanges made of aluminium for knife sizes up to Ø 300 x 2,1 mm
- Flange speed: 1.350 rpm

Turn on and off of the drive motor directly on motor terminal box.

Drive motor: 0,37 kW, 400 V, 50 Hz.

## **Special design**

Also available as rack model, type DSMS.

## **MZE Maschinenbau GmbH & Co. KG**

Siemensstr. 21  
65779 Kelkheim / Germany  
Tel.: +49 6195 9942-0  
Fax: +49 6195 9942-30  
Email: [info@kela-group.de](mailto:info@kela-group.de)  
Internet: [www.kela-group.de](http://www.kela-group.de)